





















5300 Product Range

	5331	5333	5334	 5335	 5337	5350
RTD/R transmitter	✓	✓		✓	✓	✓
TC/mV transmitter	✓		✓	✓	✓	✓
Galvanic isolation	1500 VAC		1500 VAC	1500 VAC	1500 VAC	1500 VAC
Channels	1	1	1	1	1	1
Basic accuracy Pt100	<± 0.2°C	<± 0.3°C		<± 0.1°C	<± 0.1°C	<± 0.1°C
Temperature coefficient *)	<± 0.01%	<± 0.01%	<± 0.01%	<± 0.005%	<± 0.005%	<± 0.002%
NAMUR NE 21 A	✓		✓	✓	✓	✓
DIN form B housing	✓	✓	✓	✓	✓	✓
Analog output	✓	✓	✓	✓	✓	
Digital output				 	 	  
PReset programming	✓	✓	✓	✓	✓	
Bus programming						✓

*) % of span/°C

6300 Product Range

	6331	6333	6334	 6335	 6337	6350
RTD/R transmitter	✓	✓		✓	✓	✓
TC/mV transmitter	✓		✓	✓	✓	✓
Galvanic isolation	1500 VAC		1500 VAC	1500 VAC	1500 VAC	1500 VAC
Channels	1&2	1&2	1&2	1&2	1&2	1&2
Basic accuracy Pt100	<± 0.2°C	<± 0.3°C		<± 0.1°C	<± 0.1°C	<± 0.1°C
Temperature coefficient *)	<± 0.01%	<± 0.01%	<± 0.01%	<± 0.005%	<± 0.005%	<± 0.002%
NAMUR NE 21 A	✓		✓	✓	✓	✓
DIN rail mounting	✓	✓	✓	✓	✓	✓
Analog output	✓	✓	✓	✓	✓	
Digital output				 	 	  
mA to bus communication				✓	✓	✓
PReset programming	✓	✓	✓			
Bus programming				✓	✓	

*) % of span/°C

